



HT-900ML

热转印机

Heat Transfer Machine



仅供参考样品
Sample for reference



特色 Features:

- 人机界面控制，操作简单，工作台左右移动采用伺服马达驱动，确保机器运行稳定可靠。
PLC is used for control together with LCD displaying to ensure high reliability and stability.
- 胶辊以直线与加工面接触，克服了烫印纸与加工面之间含残存空气的缺点，能获得均匀美观的加工面。
Rubber roller contacts with substrate linearly during transfer to remove remained air and to get even and beautiful image.
- 设有高精度光电管（电眼），对带接点的转印纸进行跟踪定位控制，对无接点的转印纸采用定时送纸的方法。
Photoelectric cell controls transfer position and regularly paper sending;
- 转印面积大，工作台行程可调，方便转印不同长度的工件。
Large transfer printing area. Worktable stroke can be adjusted to suit for different length of work piece.
- 烫印头位置高低可调，满足不同高度工件的需要。
Height of stamping head can be adjusted;
- 自动送纸、收纸、并可调。
Auto and adjustable paper sending and collecting.

技术参数 Technical Data:

- 砑胶辊尺寸: $\Phi 100 \times 300$ (mm)
Rubber roller size
- 工作台最大行程: 900 (mm)
Max. worktable stroke
- 最大转印面积: 270x860 (mm)
Max. transferring area
- 最快印刷速度: 300 (pcs/hr)
Max. Printing Speed
- 最大烫印高度: 180 (mm)
Max. stamping height
- 耗气量: 50 (L/min)
Air Consumption:
- 额定功率: 3500 (w)
Rated power
- 外形尺寸: 2500x710x1755 (mm)
Outline Dimensions:
- 重量: 450 (kg)
Weight



恒晖氣動工程有限公司

Ever Bright Printing Machine Fty Ltd
地址: 香港葵涌圳邊街1號南華工業大廈18樓
18/F, South China Ind Bldg., No.1 Chun Pin St., Kwai Chung, Hong Kong
Tel: (852) 2421 8573 (8 Lines) Fax: (852) 2489 2512, 2423 1428
http://www.ever-bright.com e-mail: info@ever-bright.com



广东恒晖彩印机器设备厂有限公司

Guangdong Ever Bright Printing Machine Fty Ltd
地址: 广东省东莞市凤岗镇竹尾田易发路2号恒晖工业中心
电话: (0769) 38983222 传真: (0769) 87512888 87518038
http://www.everbgt.com e-mail: eb@everbgt.com